

ADOBE® INDESIGN® CS3

TAGGED TEXT

USER GUIDE

© 2007 Adobe Systems Incorporated. All rights reserved.

Adobe® InDesign® CS3 User Guide for Windows® and Macintosh

If this guide is distributed with software that includes an end user agreement, this guide, as well as the software described in it, is furnished under license and may be used or copied only in accordance with the terms of such license. Except as permitted by any such license, no part of this guide may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, recording, or otherwise, without the prior written permission of Adobe Systems Incorporated. Please note that the content in this guide is protected under copyright law even if it is not distributed with software that includes an end user license agreement.

The content of this guide is furnished for informational use only, is subject to change without notice, and should not be construed as a commitment by Adobe Systems Incorporated. Adobe Systems Incorporated assumes no responsibility or liability for any errors or inaccuracies that may appear in the informational content contained in this guide.

Please remember that existing artwork or images that you may want to include in your project may be protected under copyright law. The unauthorized incorporation of such material into your new work could be a violation of the rights of the copyright owner. Please be sure to obtain any permission required from the copyright owner.

Any references to company names in sample templates are for demonstration purposes only and are not intended to refer to any actual organization.

Adobe, the Adobe logo, Acrobat, Adobe Bridge, Adobe Caslon, After Effects, Creative Suite, Dreamweaver, Flash, GoLive, Illustrator, InCopy, InDesign, the OpenType logo, PageMaker, Photoshop, PostScript, PostScript 3, Reader, and Version Cue are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Mac OS and QuickTime are trademarks of Apple Inc., registered in the United States and other countries. OpenType, Vista, and Windows are trademarks of Microsoft Corporation registered in the U.S. and/or other countries. Java is a trademark or registered trademark of Sun Microsystems, Inc. in the United States and other countries. Pantone, Inc. is the copyright owner of color data and/or software which are licensed to Adobe Systems Incorporated to distribute for use only in combination with Adobe InDesign. PANTONE Color Data and/or Software shall not be copied onto another disk or into memory unless as part of the execution of Adobe InDesign. All other trademarks are the property of their respective owners.

Certain Spelling portions of this product are based on Proximity Linguistic Technology. ©Copyright 1990 Merriam-Webster Inc. ©Copyright 1990 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 2003 Franklin Electronic Publishers Inc. ©Copyright 2003 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. Legal Supplement ©Copyright 1990/1994 Merriam-Webster Inc./Franklin Electronic Publishers Inc. ©Copyright 1994 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1990/1994 Merriam-Webster Inc./Franklin Electronic Publishers Inc. ©Copyright 1997 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA ©Copyright 1990 Merriam-Webster Inc. ©Copyright 1993 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 2004 Franklin Electronic Publishers Inc. ©Copyright 2004 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1991 Dr. Lluís de Yzaguirre I Maura ©Copyright 1991 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1990 Munksgaard International Publishers Ltd. ©Copyright 1990 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1990 Van Dale Lexicografie bv ©Copyright 1990 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1995 Van Dale Lexicografie bv ©Copyright 1996 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1990 IDE a.s. ©Copyright 1990 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1992 Hachette/Franklin Electronic Publishers Inc. ©Copyright 2004 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1991 Text & Satz Datentechnik ©Copyright 1991 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 2004 Bertelsmann Lexikon Verlag ©Copyright 2004 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 2004 MorphoLogic Inc. ©Copyright 2004 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1990 William Collins Sons & Co. Ltd. ©Copyright 1990 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1993-95 Russicon Company Ltd. ©Copyright 1995 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 2004 IDE a.s. ©Copyright 2004 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. The Hyphenation portion of this product is based on Proximity Linguistic Technology. ©Copyright 2003 Franklin Electronic Publishers Inc. ©Copyright 2003 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1984 William Collins Sons & Co. Ltd. ©Copyright 1988 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1990 Munksgaard International Publishers Ltd. ©Copyright 1990 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1997 Van Dale Lexicografie bv ©Copyright 1997 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1984 Editions Fernand Nathan ©Copyright 1989 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1983 S Fischer Verlag ©Copyright 1997 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1989 Zanichelli ©Copyright 1989 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1989 IDE a.s. ©Copyright 1989 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1990 Espasa-Calpe ©Copyright 1990 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA. ©Copyright 1989 C.A. Stromberg AB. ©Copyright 1989 All rights reserved. Proximity Technology A Division of Franklin Electronic Publishers, Inc. Burlington, New Jersey USA.

The Spelling portion of this product is based on Proximity Linguistic Technology. Color-database derived from Sample Books © Dainippon Ink and Chemicals, Inc., licensed to Adobe Systems Incorporated. Portions © The Focoltone Colour Systems, and used under license.

This product includes software developed by the Apache Software Foundation (www.apache.org).

Portions © 1984-1998 Faircom Corporation. All rights reserved. Portions copyrighted by Trumatch, Inc. and used under license.

PANTONE® Colors displayed in the software application or in the user documentation may not match PANTONE-identified standards. Consult current PANTONE Color Publications for accurate color. PANTONE® and other Pantone, Inc. trademarks are the property of Pantone, Inc. © Pantone, Inc., 2006

This product contains either BISAPE and/or TIPEM software by RSA Data Security, Inc. Copyright (c) 1994 Hewlett-Packard Company. Permission to use, copy, modify, distribute and sell this software and its documentation for any purpose is hereby granted without fee, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation. Hewlett-Packard Company makes no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

Copyright (c) 1996, 1997 Silicon Graphics Computer Systems, Inc. Permission to use, copy, modify, distribute and sell this software and its documentation for any purpose is hereby granted without fee, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation. Silicon Graphics makes no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

Notice to U.S. Government End Users: The Software and Documentation are "Commercial Items," as that term is defined at 48 C.F.R. §2.101, consisting of "Commercial Computer Software" and "Commercial Computer Software Documentation," as such terms are used in 48 C.F.R. §12.212 or 48 C.F.R. §227.7202, as applicable. Consistent with 48 C.F.R. §12.212 or 48 C.F.R. §227.7202-1 through 227.7202-4, as applicable, the Commercial Computer Software and Commercial Computer Software Documentation are being licensed to U.S. Government end users (a) only as Commercial Items and (b) with only those rights as are granted to all other end users pursuant to the terms and conditions herein. Unpublished-rights reserved under the copyright laws of the United States. Adobe agrees to comply with all applicable equal opportunity laws including, if appropriate, the provisions of Executive Order 11246, as amended, Section 402 of the Vietnam Era Veterans Readjustment Assistance Act of 1974 (38 USC 4212), and Section 503 of the Rehabilitation Act of 1973, as amended, and the regulations at 41 CFR Parts 60-1 through 60-60, 60-250, and 60-741. The affirmative action clause and regulations contained in the preceding sentence shall be incorporated by reference.

Adobe Systems Incorporated, 345 Park Avenue, San Jose, California 95110, USA.

Contents

Adobe InDesign Tagged Text

Tagged text	1
InDesign tags	3

Adobe InDesign Tagged Text

You can use tags in Adobe® InDesign® or Adobe InCopy® to import and export formatting attributes with text-only files. These tags, or codes, indicate style and list definitions as well as the character- and paragraph-level attributes you want to apply to text.

Tagged text

When you import a tagged text file, InDesign or InCopy reads the tag codes and applies the attributes automatically. When you export formatted text, you can generate the tag codes so that you can later edit the tags and import the information with formatting intact.

<p>Anton Guitars Open the case for the <i>first time</i> and take in the sights and smells of your hand-made instrument. See the way the light reflects off the handrubbed satin finish. Breath in the perfume of the finest exotic tone woods. Then, finally, take it in your hands and begin to play.</p>	<pre><ASCII-MAC> <DefineParaStyle:Head 1=<cTypeface:Plain> <cSize:24.0><cLeading:18.0><cFont:Gill Sans>> <ColorTable:=<Black:COLOR:CMYK:Process:0.0000, 0.0000,0.0000,1.0000>> <ParaStyle:Head 1>Anton Guitars <ParaStyle:><cTypeface:><cFont:Minion>Open the case for the <cTypeface:><cFont:> <cTypeface:Italic><cFont:Minion>first time <cTypeface:><cFont:><cTypeface:><cFont:Minion> and take in the sights and smells of your hand-made instrument. See the way the light reflects off the handrubbed satin finish. Breath in the perfume of the finest exotic tone woods. Then, finally, take it in your hands and begin to play.</pre>
---	--

Formatted InDesign document (left) and exported tagged text file (right), with tags shown in red

Only InDesign and InCopy can read InDesign tags. InDesign cannot read tagged text files formatted in Adobe PageMaker® and QuarkXPress®.

For a more up-to-date version of this Tagged Text PDF, visit www.adobe.com/go/learn_id_taggedtext.

Import and export tags

All tags begin with the less-than character (<) and end with the greater-than character (>). Type the tag immediately before the text you want to format. For paragraph-level attributes, type the tag at the start of the paragraph. For character-level attributes, type the tag at the start of the text you want to change. Most type attributes you specify remain in effect until you use codes to cancel them or until you apply other attributes. For example, to apply underlining to one word in a paragraph, you type <cUnderline:1> before the word and <cUnderline:> after the word.

 To learn about using tag codes, export text with tags from a formatted document. Then view the exported text in a word-processing application or text editor to see how the attributes are transformed into tag codes. You can then edit and add tags before you import the tagged text file.

Export InDesign text as tagged text

- 1 Using the Type tool, click an insertion point in the story you want to export, or select the range of text you want to export.
- 2 Choose File > Export.

- 3 For Save As Type (Microsoft® Windows®) or Format (Apple® Mac OS®), select Adobe InDesign Tagged Text.
- 4 Specify a name and location for the file, and click Save. (If you're saving the file using Mac OS, add a .txt extension to the end of the filename if you want to open the file in Windows.)
- 5 In the Adobe InDesign Tags Export Options dialog box, specify the following options:
 - Select Verbose to show the tags in long form, such as <StrokeColor:Green> or Abbreviated to show the tags in short form, such as <csc:Green>.
 - Select the encoding format, such as ASCII (the most common format for representing English characters as numbers), ANSI (a collection of many international characters and special punctuation marks that can be inserted using the Alt/Option key), Unicode (a standard that supports most language characters, including non-European languages), Shift-JIS (MS-Kanji for Japanese characters), GB 18030 (the official character set of the People's Republic of China), Big 5 (encoding for Traditional Chinese characters), and KSC5601 (encoding for Korean characters).
- 6 Click OK.

The story text is exported as a text file. You can use a word-processing application or a text editor to open and edit the tagged text file.

Import tagged text

- 1 Open the document into which you will place the tagged text, and choose File > Place.
- 2 Locate and select the text-only tagged file.
- 3 If desired, select Show Import Options.
- 4 Click Open.
- 5 If you selected Show Import Options in the Place dialog box, select any of the following:
 - Use Typographer's Quotes** Ensures that imported text includes left and right quotation marks (“ ”) and apostrophes (') instead of straight quotation marks (" ") and apostrophes (').
 - Remove Text Formatting** Removes formatting such as typeface, type color, and type style from the imported text.
 - Resolve Text Style Conflicts Using** Lets you specify which character or paragraph style is applied when there is a conflict between the style in the tagged text file and the style in your document. Select Publication Definition to use the definition that already exists for that style name in the document. Select Tagged File Definition to use the style as defined in the tagged text. This option creates another instance of the style with “copy” appended to its name in the Character Style or Paragraph Style panel.
 - Show List Of Problem Tags Before Place** Displays a list of unrecognized tags. If a list appears, you can choose to cancel or continue the import. If you continue, the file may not look as expected.
- 6 Click OK.

The text appears at the insertion point or replaces selected text. If there is no text selection or insertion point, a loaded text icon appears. You can click inside an existing frame to place the text inside it, or you can click or drag to create a new text frame.

Specifying numeric values in tags

Note the following tips for specifying numeric values or text within a tag:

- In the Tag Name column for the following tables, each tag includes the value type. *String* includes a list of characters, such as the name of a color. (When the information is a text string, the case of the characters doesn't matter, unless you're typing a specific color or style name.) *Integer* includes only whole numbers for values, such as the number of drop-cap characters. *Real* can include any number, such as "23.578." *Boolean* includes on/off toggle values: "0" for off and "1" for on. *Enum* includes only specific string values, such as "Small Caps." *Definition* includes valid names of defined styles and lists.
- Numeric measurements are expressed as points.
- If you create a tagged text file in a word-processing application or text editor, any characters, tabs, and spaces you type outside the angle brackets (< >) appear in the document when the file is placed. To begin a new paragraph with no paragraph style assigned, type <ParaStyle:> on a new line.
- To return an attribute to its default state, type the attribute name followed by a colon (:). For example, to return to the default leading value, type <cLeading:>.

InDesign tags

For a more up-to-date version of these tags, visit www.adobe.com/go/learn_id_taggedtext.

Start file and definition tags

When you export text as tagged text, the text file includes a start tag that describes the encoding format (such as <ASCII-WIN>) and a color table tag (<ColorTable>) that defines the colors, tints, and gradients in your document. If you use paragraph and character styles, variables, table and cell styles, or defined lists in exported text, definition tags for those items appear.

Note: If you create a tagged text file from scratch, you must include a tag that describes the encoding format (such as <ASCII-MAC>) at the beginning of the text file. You must type the following text at the top of a text file you want InCopy to treat as tagged: <ASCII-WIN> for files created in Windows or <ASCII-MAC> for files created in Mac OS. If you use an encoding format other than ASCII, insert the name of that format in place of ASCII (for example, <UNICODE-MAC>).

Attribute	Format	Examples and notes
Start file tag	<Encodingformat-Platform>	<ASCII-MAC> Specify the encoding format (ASCII, ANSI, UNICODE, SJIS, CGB18030, BIG5, or KSC5601) followed by the platform (MAC or WIN).
Color table	<ColorTable:=<Swatch name 1:Swatch Type (COLOR, TINT, GRAD, or MIXED):Color Type (CMYK, RGB, LAB, or MIXED):Color Mode (Process, Spot, or Mixed):Values of color, tint, or gradient> <Swatch name 2>...> A COLOR swatch requires 4 values for CMYK and 3 values for RGB and LAB. GRADIENT syntax: <Gradient name: GRAD:Fill type:StopPosition1;StopColor1;Midpoint1 StopPosition2;StopColor2;Midpoint2> TINT syntax: <Base Color:TINT:Tint value> MIXED Ink Syntax: <MixedInk Name:MIXED:MIXED:Mixed:Component1Name, Component2Name:Component1value,Component2value>	<ColorTable:= <Black:COLOR:CMYK:Process:0,0,0,1> <Green:COLOR:CMYK:Process:1,0,1,0> <Blue:COLOR:CMYK:Process:1,1,0,0> <G/B:GRAD:Linear:0.0;Green;0.5 1.0;Blue;0.5> <Blue:TINT:Blue;20>> <MixedInk1:MIXED:MIXED:Mixed:Green,Blue:1.00,0.5> The color table is a list of all colors, tints, and gradients defined in the Swatches panel and used in the text. You can use the abbreviation <Table>.
Paragraph style definition	<DefineParaStyle:Style group name::Paragraph style name= <attr1><attr2>...> A paragraph style definition includes the character- and paragraph-level attributes listed later in this document, as well as <Nextstyle:style name> and <BasedOn:style name>	<DefineParaStyle:Style Group 1:Heading 1=<Nextstyle:Body Text> <cFont:AdobeGaramond><cSize:18> <pBodyAlignment:Center>> The paragraph style definition includes a list of all styles defined in the Paragraph Styles panel and used in the text.
Paragraph style applied	<ParaStyle:Paragraph style name>	<ParaStyle:Heading 1> The tag <ParaStyle:> starts a new paragraph with no paragraph style. You can use the abbreviation <pStyle>.
Character style definition	<DefineCharStyle:Style group name::Char style name= <char attr1><char attr2>...> A character style definition includes the character-attributes listed later in this document, as well as <Nextstyle:style name>.	<DefineCharStyle:Style Group 1:Emphasis=<Nextstyle:Emphasis> <cTypeface:Italic>> The character style definition includes a list of all styles defined in the Character Styles panel and used in the text.
Character style applied	<CharStyle:Character style name>	<CharStyle:Emphasis> The tag <CharStyle:> ends the character style definition.
Table style definition	<DefineTableStyle:Style group name:table style name=<table attr1><table attr2>...<cell style>...> A table style definition includes the table attributes listed later in this document followed by the cell styles used in the table style. The <BasedOn:style name> attributes can also be included.	<DefineTableStyle:Style Group 1:Income Table=<tBeforeSpace:6><tLastColCellStyle::Blue Fill><tLastColUseBodyCellStyle:0>>
Table style applied	<TableStyle:Table style name> The <TableStyle> tag appears before the <TableStart> tag.	<TableStyle:Income Table>

Attribute	Format	Examples and notes
Cell style definition	<p><DefineCellStyle:Style group name:cell style name=<cell attr 1><cell attr 2>...></p> <p>A cell style definition includes the cell attributes listed later in this document, as well as <BasedOn:style name>.</p>	<p><DefineCellStyle:Style Group 1:Blue Fill:<tCellFillColor:C\=75 M\=0 Y\=0 K\=0>></p>
Cell style applied	<CellStyle:cell style name>	<p><CellStyle:Blue Fill></p> <p>The <CellStyle> tag appears after the <CellStart> tag, and the <End:CellStyle> tag appears after the <CellEnd> tag.</p>
Define list	<p><DefineListStyle:list name=<list attr 1><list attr 2>></p> <p>The two attributes you can include are <ContinuesAcrossStories:0 or 1> and <ContinuesAcrossDocuments:0 or 1> (0=off; 1=on)</p>	<p><DefineListStyle:Level 1=<ContinuesAcrossStories:0>></p>
Variable definition	<p><DefineTextVariable:variable name=<TextVarType:type><var attr 1><var attr 2>...></p> <p>A variable style definition includes the type of variable and variable attributes listed later in this document.</p>	<p><DefineTextVariable:Chapter Titles=<TextVarType:ChapterNum><tvTextBefore:Chapter <tvDelEndPunctuation>></p> <p>TextVarType attributes include CreateDate, ModDate, OutputDate, PageCount, FileName, CustomText, ChapterNum, ParaStyle, and CharStyle</p>
Variable inserted	<TextVarName:var name>	<TextVarName:Chapter Number>

Tags for formatting characters and paragraphs

The following tables describe character- and paragraph-level tags.

Character-level tags

Attribute	Tag name	Tag abbr.	Examples and notes
Alternate glyph	cAlternateGlyph:Integer	caltg	<p><cAlternateGlyph:3></p> <p>Alternate glyphs for OpenType or Asian fonts such as Tekton Pro MM appear in the Glyphs panel. In this example, 3 represents the third alternate glyph in the pop-up panel.</p>
Auto pair kerning	cAutoPairKern:String	capk	<p><cAutoPairKern:Optical></p> <p>This tag can include Optical or Metrics (default).</p>
Baseline shift	cBaselineShift:Real	cbs	<p><cBaselineShift:3></p> <p>This value can be between -5000 and 5000 points.</p>
Case	cCase:Enum	ccase	<p><cCase:Small Caps></p> <p>Valid values include Small Caps, All Caps, Caps To Small Caps, or Normal (default). Caps To Small Caps is an OpenType font attribute.</p>
Character alignment	cHang:Enum	ch	<p><cHang:Top></p> <p>Valid values include EmTop, EmCenter (default), EmBottom, Baseline, ICFTop, and ICFBottom.</p>

Attribute	Tag name	Tag abbr.	Examples and notes
Character skew	<i>cSkew:Real</i>	csk	<cSkew:-25> The value represents the percentage of character skew from 85 to -85 degrees.
Color: color tint	<i>cColorTint:Real</i>	cct	<cColorTint:80> Specify a tint percentage.
Color: character fill	<i>cColor:String or Color Definition</i>	cc	<cColor:Green> or <cColor:COLOR:RGB:Process: 0.5,1,0> This tag can include tints, gradients, and unnamed colors. The default color is Black.
Color: character stroke	<i>cStrokeColor:String or Color Definition</i>	csc	<cStrokeColor:Green> or <cColor:COLOR:RGB:Process:0.5,1,0> This tag can include tints, gradients, and unnamed colors. The default color is None.
Color: fill gradient angle	<i>cGradientAngle:Real</i>	cga	<cGradientAngle:-45> Angle of linear gradient fill from -180 to 180 degrees.
Color: fill gradient center	<i>cGradientCenter:Real,Real</i>	cgc	<cGradientCenter:-145,-145> This tag indicates the x and y values of the center point of a radial gradient or the starting point of a linear gradient.
Color: fill gradient length	<i>cGradientLength:Real</i>	cgl	<cGradientLength:2> This tag indicates the length of a linear gradient ramp or radius of a radial gradient.
Color: stroke gradient angle	<i>cStrokeGradientAngle:Real</i>	csga	<cStrokeGradientAngle:-45> Angle of linear gradient fill from -180 to 180 degrees.
Color: stroke gradient center	<i>cStrokeGradient-Center:Real,Real</i>	csgs	<cStrokeGradientCenter:-145,-145> This tag indicates the x and y values of the center point of a radial gradient or the starting point of a linear gradient.
Color: stroke gradient length	<i>cStrokeGradientLength:Real</i>	csgl	<cStrokeGradientLength:2> This tag indicates the length of a linear gradient ramp or radius of a radial gradient.
Color: stroke tint	<i>cStrokeTint:Real</i>	cst	<cStrokeTint:80> Specify a tint percentage.
Color: stroke weight (thickness)	<i>cStrokeWeight:Real</i>	csw	<cStrokeWeight:0.5> Specify a value between 0 and 800.
Font: family	<i>cFont:String</i>	cf	<cFont:Adobe Garamond> Specify only the family name. To complete the font information, also use <cSize> and <cTypeface>.
Font: point size	<i>cSize:Real</i>	cs	<cSize:18> Specify a point size between 0.1 and 1296.

Attribute	Tag name	Tag abbr.	Examples and notes
Font: typeface	cTypeface:String	ct	<cTypeface:Italic> The values for this tag depend on which font is used. For example, Times New Roman uses Regular while Helvetica uses Plain.
ILG shift	cILGShift:Real	cilgs	<cILGShift:200> Specify a value between -8640 and 8640.
Kerning	cKerning:Real	ck	<cKerning:50>
Language	cLanguage:String	clang	<cLanguage:Portuguese: Brazilian> To use a valid string, type the name of the language as it appears in the Character panel.
Leading	cLeading:Real	cl	<cLeading:18> This tag lets you specify a leading value between 0 and 5000. To use default auto leading, leave value empty (<cLeading:>).
Leading model	cLeadingModel:Center Down	cleadmod	CenterDown signifies the leading will be measured from the center of the current line to the center of the next line.
Ligatures	cLigatures:Boolean	clig	<cLigatures:1> 1=on (default), 0=off
No break	cNoBreak:Boolean	cnb	<cNoBreak:1> 1=on, 0=off (default)
Next break character	cNextXChars:Enum	cnxc	<cNextXChars:Column> Valid values include NoForcedBreak (default), Column-Break, PageBreak, BoxBreak, OddPageBreak, and EvenPageBreak.
Old style figures	cOldStyleFigures:Boolean	cosf	<cOldStyleFigures:1> 1=on, 0=off (default)
OpenType: figure style	cFigureStyle:Enum	cfs	<cFigureStyle:Proportional Oldstyle> Valid values include Tabular Lining (default), Proportional Oldstyle, Proportional Lining, Figure Style, and Tabular Oldstyle.
OpenType: contextual alternate	cOTFContAlt:Boolean	cotfsalt	<cOTFContAlt:0> 1=on (default), 0=off
OpenType: discretionary ligatures	cOTFDiscLig:Boolean	cotfdl	<cOTFDiscLig:1> 1=on, 0=off (default)
OpenType: feature list	cOTFeatureList:String	cotfl	<cOTFeatureList:zero,1>
OpenType: fractions	cOTFFractions:Boolean	cotff	<cOTFFractions:1> 1=on, 0=off (default)
OpenType: locale	cOTFLocale:Boolean	cotflocl	<cOTFLocale:1> 0=off (default), 1=on

Attribute	Tag name	Tag abbr.	Examples and notes
OpenType: mark position	cOTFMarkPos: <i>Boolean</i>	cotfmark	<cOTFMarkPos:1> 0=off (default), 1=on
OpenType: position	cPosition: <i>Enum</i>	cp	<cPosition:Numerator> Valid values include None (default), Superior, Inferior, Numerator, and Denominator.
OpenType: position form	cOTFPositionForm: <i>Enum</i>	cotfposform	<cOTFPositionForm:Initial> Valid values include Off, Automatic, Initial, Medial, Final, and Isolated.
OpenType:proportional metrics	cOTFUseProportional Metric: <i>Boolean</i>	cotfupm	<cOTFUseProportionalMetric:1> 1=on, 0=off (default)
OpenType:roman italics	cOTFRomanItalics: <i>Boolean</i>	cotfri	<cOTFRomanItalics:1> 1=on, 0=off (default)
OpenType: ordinals	cOTFOrdinal: <i>Boolean</i>	cotfo	<cOTFOrdinal:1> 1=on, 0=off (default)
OpenType: slash zero	cOTFSlashZero: <i>Boolean</i>	cotfsz	<cOTFSlashZero:1> 1=on, 0=off (default)
OpenType: stylistic sets	cOTFStylisticSets: <i>Integer</i>	cotfss	<cOTFStylisticSets:8>
OpenType: titling alternates	cOTFTitlAl: <i>Boolean</i>	cotfttl	<cOTFTitlAl:1> 1=on, 0=off (default)
OpenType:swash alternates	cOTFSwaAlt: <i>Boolean</i>	cotfsalt	cOTFSwaAlt:1> 1=on, 0=off (default)
Next break character	cNextXChars: <i>Enum</i>	cnxc	<cNextXChars:Column> Valid values include NoForcedBreak, ColumnBreak, Page-Break, FrameBreak, OddPageBreak, and EvenPageBreak. NoForcedBreak is the default value.
No break	cNoBreak: <i>Boolean</i>	cnb	<cNoBreak:1> 1=on, 0=off (default)
Old style figures	cOldStyleFigures: <i>Boolean</i>	cosf	<OldStyleFigures:1> 1=on, 0=off (default)
Overprint character fill	cOverprint: <i>Boolean</i>	co	<cOverprint:1> 1=on, 0=off (default)
Overprint character stroke	cStrokeOverprint: <i>Boolean</i>	cso	<cStrokeOverprint:1> 1=on, 0=off (default)
Prev/Next page number	cPageNumType: <i>Enum</i>	cpnt	<cPageNumType:Next> Valid values include Next, Previous, and Current. Current is the default value.

Attribute	Tag name	Tag abbr.	Examples and notes
Rotate Character	cCharRotate: <i>Real</i>	cchr	<cCharRotate:45> Specify a value between -360 and 360 to rotate the character on its center axis. Positive values rotate the character counterclockwise.
Scaling:affects line height	cScaleAffectsLineHeight: <i>Boolean</i>	csclineh	<cScaleAffectsLineHeight:1> 1=on, 0=off (default)
Scaling: horizontal	cHorizontalScale: <i>Real</i>	chs	<cHorizontalScale:2> The value 1.0 equals 100%. You can use values between 1% (.01) and 1000% (10.0).
Scaling: vertical	cVerticalScale: <i>Real</i>	cvs	<cVerticalScale:2> The value 1.0 equals 100%. You can use values between 1% (.01) and 1000% (10.0).
Small cap percentage	cSmallCapPercentage: <i>Real</i>	cscap	<cSmallCapPercentage:70> Specify a percentage value.
Strikethrough	cStrikethru: <i>Boolean</i>	cstrike	<cStrikethru:1> 1=on, 0=off (default)
Strikethrough gap color	cStrikethroughGapColor: <i>Real</i>	cugc	<cStrikethroughGapColor:C\=100 M\=0 Y\=0 K\=0>
Strikethrough gap overprint	cStrikethroughGapOverprint: <i>Boolean</i>	cugo	<cStrikethroughGapOverprint:1> 1=on, 0=off (default)
Strikethrough gap tint	cStrikethroughGapTint: <i>Real</i>	cugt	<cStrikethroughGapTint:30>
Strikethrough offset	cStrikethroughOffset: <i>Real</i>	cuoff	<cStrikethroughOffset:3>
Strikethrough weight offset	cStrikethroughWeightOffset: <i>Real</i>	cuwoff	<cStrikethroughWeightOffset:3>
Strikethrough type	cStrikethroughType: <i>Definition</i>	cutype	<cStrikethroughType:ThickThin>
Superscript or subscript character position	cPosition: <i>Enum</i>	cp	<cPosition:Superscript> Valid values include Superscript, Subscript, or Normal (default).
Tracking	cTracking: <i>Real</i>	ctk	<cTracking:50> Specify a value between -1000.0 and 10000 (1000ths of an em).
Underline	cUnderline: <i>Boolean</i>	cu	<cUnderline:1> 1=on, 0=off (default)
Underline gap color	cUnderlineGapColor: <i>Real</i>	cugc	<cUnderlineGapColor:C\=100 M\=0 Y\=0 K\=0>
Underline gap overprint	cUnderlineGapOverprint: <i>Boolean</i>	cugo	<cUnderlineGapOverprint:1> 1=on, 0=off (default)
Underline gap tint	cUnderlineGapTint: <i>Real</i>	cugt	<cUnderlineGapTint:30>
Underline offset	cUnderlineOffset: <i>Real</i>	cuoff	<cUnderlineOffset:3>

Attribute	Tag name	Tag abbr.	Examples and notes
Underline weight offset	cUnderlineWeight-Offset: <i>Real</i>	cuwoff	<cUnderlineWeightOffset:3>
Underline type	cUnderlineType: <i>Definition</i>	cutype	<cUnderlineType:ThickThin>
Multi-master optical size	cMultiMasterOptical-Size: <i>Real</i>	cmmos	<cMultiMasterOpticalSize:10>

Paragraph-level tags

Attribute	Tag name	Tag abbr.	Examples and notes
Align to baseline grid	pAlignToGrid: <i>Boolean</i>	patg	<pAlignToGrid:1> 1=on, 0=off (default)
Alignment of text in paragraph	pTextAlignment: <i>Enum</i>	pta	<pTextAlignment:Center> Valid values include Left, Right, Center, JustifyLeft, JustifyRight, JustifyCenter, JustifyFull, AwayFromSpine, and ToSpine. Left is the default value.
Balance ragged lines	pBalanceLines: <i>Boolean</i>	pbl	<pBalanceLines:1> 0=off (default), 1=on (Vee shape), 2=Equal, 3=Pyramid The user interface lets you turn balanced lines on or off. The 2 and 3 values are available only for scripting purposes.
Drop cap details	pDropCapDetail: <i>String</i>	pdcdetail	<pDropCapDetail:LeftGlyphEdge\,Descenders> Include LeftGlyphEdge and/or Descenders to turn on Align Left Edge and Scale for Descenders, respectively.
Drop cap: number of characters	pDropCapCharacters: <i>Integer</i>	pdcc	<pDropCapCharacters:1>
Drop cap: number of lines	pDropCapLines: <i>Integer</i>	pdcl	<pDropCapLines:3>
First line indent	pFirstLineIndent: <i>Real</i>	pfli	<pFirstLineIndent:6>
Glyph scaling: desired	pDesiredGlyphScale: <i>Real</i>	pdgs	<pDesiredGlyphScale:1.0> Specify a value between 0.5 (50%) and 2.0 (200%). The default value is 1.0 (100%).
Glyph scaling: maximum	pMaxGlyphScale: <i>Real</i>	pmaxgs	<pMaxGlyphScale:1.1> Specify a value between 0.5 (50%) and 2.0 (200%). The default value is 1.0 (100%). The Maximum value must be greater than the Desired value.
Glyph scaling: minimum	pMinGlyphScale: <i>Real</i>	pmings	<pMinGlyphScale:0.9> Specify a value between 50% (0.5) and 200% (2.0). The default value is 1.0 (100%). The Minimum value must be less than the Desired value.
Hyphenate all capital words	pHyphenateCapitals: <i>Boolean</i>	phc	<pHyphenateCapitals:1> 1=on, 0=off (default)
Hyphenate Last Word	pHyphenateCross-Frame: <i>Boolean</i>	phcf	<pHyphenateCrossFrame:1> 0=off (default), 1=on

Attribute	Tag name	Tag abbr.	Examples and notes
Hyphenation: hyphen limit	pHyphenationLadderLimit: <i>Integer</i>	phll	<pHyphenationLadderLimit:5> Value indicates maximum number of consecutive hyphens from 1 to 25; zero means unlimited.
Hyphenation: last word	pHyphenateLastWord: <i>Boolean</i>	phlw	<pHyphenateLastWord:0> 1=on (default), 0=off
Hyphenation: minimum number of characters after hyphen	pMinCharAfterHyphen: <i>Integer</i>	pmcah	<pMinCharAfterHyphen:3> Specify a value from 1 to 15. The value 3 is the default.
Hyphenation: minimum number of characters before hyphen	pMinCharBeforeHyphen: <i>Integer</i>	pmcbh	<pMinCharBeforeHyphen:3> Specify a value from 1 to 15. The value 3 is the default.
Hyphenation: number of characters in shortest word allowed to be hyphenated	pShortestWordHyphenated: <i>Integer</i>	pswh	<pShortestWordHyphenated:3> This range of this value is from 3 to 25. The default value is 7.
Hyphenation: on or off	pHyphenation: <i>Boolean</i>	ph	<pHyphenation:1> 1=on (default), 0=off
Hyphenation: zone	pHyphenationZone: <i>Real</i>	phz	<pHyphenationZone:48> Value (in points) is valid only if Single-line Composer is turned on. Specify a value between 0 and 8640. The default value is 36 points.
Ignore Optical Margin Alignment	pIgnoreEdgeAlign: <i>Boolean</i>	piea	<pIgnoreEdgeAlign:1> 0=off (default), 1=on
Keep first n lines together (widow control)	pKeepFirstNLines: <i>Integer</i>	pkfnl	<pKeepFirstNLines:4> Specify a value from 1 to 50 (1 is equivalent to off).
Keep last lines together (orphan control)	pKeepLastNLines: <i>Integer</i>	pknl	<pKeepLastNLines:2> Specify a value from 1 to 50 (1 is equivalent to off).
Keep lines together	pKeepLines: <i>Boolean</i>	pkl	<pKeepLines:1> 1=on, 0=off (default)
Keep whole paragraph together	pKeepParaTogether: <i>Boolean</i>	pkpt	<pKeepParaTogether:1> 1=on, 0=off (default)
Keep with next lines	pKeepWithNext: <i>Integer</i>	pkwn	<pKeepWithNext:4> Specify a value from 0 to 5 (0 means off).
Last line right indent	pLastRightIndent: <i>Real</i>	plri	<pLastRightIndent:6>
Leading: autoleading percentage	pAutoLeadPercent: <i>Real</i>	palp	<pAutoLeadPercent:1.2> The value 1.0 equals 100%. Specify a value between 0 and 5 (500%). The default value is 1.75 (175%) for text in plain text frames and 1 (100%) for text in frame grids.
Left indent	pLeftIndent: <i>Real</i>	pli	<pLeftIndent:6>

Attribute	Tag name	Tag abbr.	Examples and notes
Letterspacing: desired	pDesiredLetterspace: <i>Real</i>	pdl	<pDesiredLetterspace:1.0> Specify a value between -1.0 (-100%) and 50 (500%). The default value is 1.0 (100%).
Letterspacing: maximum	pMaxletterspace: <i>Real</i>	pmaxl	<pMaxletterspace:1.2> The value 1.0 equals 100%. Specify a value between the desired letterspacing value and 5 (500%). The default value is 0.
Letterspacing: minimum	pMinLetterspace: <i>Real</i>	pminl	<pMinLetterspace:0.9> The value 1.0 equals 100%. Specify a value between -1 (-100%) and the desired letterspacing value. The default value is 0%.
Nested (run-in) styles	pRunInStyles: <i>Enum</i>	prunin	<pRunInStyles:Character Style 1\,Words\,1\1;Character Style 2\,Forced Line Break\,1\,0\;> Loop example: <pRunInStyles:Character Style 1\,Words\,1\1;Character Style 2\,Forced Line Break\,1\,0\;\[Repeat]\,RI loopback\,2,1\;>
Page or columns break before paragraph	pBreakBefore: <i>Enum</i>	pbb	<pBreakBefore:Column Break> This tag can include Page, OddPage, EvenPage, Column, or None.
Paragraph rule above color	pRuleAboveColor: <i>String</i>	prac	<pRuleAboveColor:Black> This value indicates the color for the rule (line) above the paragraph. This string value must be a color name (not an unnamed color definition).
Paragraph rule above gap color	pRuleAboveGapColor: <i>String</i>	pragc	<pRuleAboveGapColor:Blue>
Paragraph rule above keep in frame	pRuleAboveKeepIn-Frame: <i>Boolean</i>	prakif	<pRuleAboveKeepInFrame:1> 1=on, 0=off (default)
Paragraph rule above tint	pRuleAboveTint: <i>Real</i>	prat	<pRuleAboveTint:80> This value indicates the tint for the rule (line) above the paragraph. The value must be between 0 and 100.
Paragraph rule above gap tint	pRuleAboveGapTint: <i>Real</i>	pragt	<pRuleAboveGapTint:80>
Paragraph rule above gap overprint	pRuleAboveGap Overprint: <i>Boolean</i>	prago	<pRuleAboveGapOverprint:1> 1=on, 0=off (default)
Paragraph rule above stroke type	pRuleAboveStroke-Type: <i>Enum</i>	prastype	<pRuleAboveStrokeType:ThickThin>
Paragraph rule above is turned on	pRuleAboveOn: <i>Boolean</i>	praon	<pRuleAboveOn:1> 1=on, 0=off (default)
Paragraph rule above left indent	pRuleAboveLeftIndent: <i>Real</i>	prali	<pRuleAboveLeftIndent:3> This value indicates the left indent from the frame edge or text edge, depending on the paragraph rule mode.

Attribute	Tag name	Tag abbr.	Examples and notes
Paragraph rule above mode	pRuleAboveMode:Enum	pram	<pRuleAboveMode:Text> This value indicates whether the paragraph rule starts at the width of the column (frame) or width of the first line of text in the paragraph. Valid values include Text and Column. Column is the default.
Paragraph rule above offset	pRuleAboveOffset:Real	prao	<pRuleAboveOffset:3> This value indicates the offset from the baseline to the paragraph rule above.
Paragraph rule above right indent	pRuleAboveRightIndent:Real	prari	<pRuleAboveRightIndent:3> This value indicates the right indent from the frame edge or text edge, depending on paragraph rule mode.
Paragraph rule above stroke	pRuleAboveStroke:Real	pras	<pRuleAboveStroke:2> This value indicates the line weight for the paragraph rule above the paragraph. Specify a value between 0 and 1000.
Paragraph rule below color	pRuleBelowColor:String	prbc	<pRuleBelowColor:Black> This value indicates the color for the rule (line) below the paragraph. This string value must be a color name (not an unnamed color definition).
Paragraph rule below gap color	pRuleBelowGapColor:String	prbgc	<pRuleBelowGapColor:Blue>
Paragraph rule below tint	pRuleBelowTint:Real	prbt	<pRuleBelowTint:80> This value indicates the tint for the rule (line) below the paragraph. The value must be between 0 and 100.
Paragraph rule below gap tint	pRuleBelowGapTint:Real	prbgt	<pRuleBelowGapTint:80>
Paragraph rule below gap overprint	pRuleBelowGapOverprint:Boolean	prbgo	<pRuleBelowGapOverprint:1> 1=on, 0=off (default)
Paragraph rule below stroke type	pRuleBelowStrokeType:Enum	prbstype	<pRuleBelowStrokeType:ThickThin>
Paragraph rule below is turned on	pRuleBelowOn:Boolean	prbon	<pRuleBelowOn:1> 1=on, 0=off (default)
Paragraph rule below left indent	pRuleBelowLeftIndent:Real	prbli	<pRuleBelowLeftIndent:3> This value indicates the left indent from the frame edge or text edge, depending on paragraph rule mode.
Paragraph rule below mode	pRuleBelowMode:Enum	prbm	<pRuleBelowMode:Text> This value indicates whether the paragraph rule starts at the width of the column (frame) or width of the first line of text in the paragraph. Valid values include Text and Column. Column is the default.
Paragraph rule below offset	pRuleBelowOffset:Real	prbo	<pRuleBelowOffset:3> This value indicates the offset from the bottom of the embox of the largest character in the line to the paragraph rule below.

Attribute	Tag name	Tag abbr.	Examples and notes
Paragraph rule below right indent	pRuleBelowRightIndent:Real	prbri	<pRuleBelowRightIndent:3> This value indicates the right indent from the frame edge or text edge, depending on paragraph rule mode.
Paragraph rule below stroke	pRuleBelowStroke:Real	prbs	<pRuleBelowStroke:2> This value indicates the line weight for the paragraph rule below the paragraph.
Paragraph rule below tint	pRuleAboveTint:Real	prbt	<pRuleAboveTint:80> This value indicates the tint for the rule (line) below the paragraph. The value must be between 0 and 100.
Right indent	pRightIndent:Real	pri	<pRightIndent:6>
Space after paragraph	pSpaceAfter:Real	psa	<pSpaceAfter:4>
Space before paragraph	pSpaceBefore:Real	psb	<pSpaceBefore:4>
Tab ruler settings	pTabRuler:x value,tab type,align on,default,leader;	ptr	<pTabRuler:48,Center,,0,;96,Char,x,0,*;144,Left,,0,;> A semicolon (;) indicates the start of a new tab setting. The x value determines the distance from the left edge of the text frame or inset in horizontal frames (top edge in vertical frames). Tab type includes Left, Center, Right, and Char (also called a decimal tab). Align on determines the character on which a decimal tab (Char) will align. Default is a boolean value (0 or 1) that indicates whether the tab is a default tab setting. Leader is a character or string of characters (such as periods or hyphens) you want to use as a tab leader.
Text composition engine	pTextComposer:String	ptc	<pTextComposer:Adobe Single-Line Composer> Specify any composer available, including the Paragraph Composer (default) and the Single-line Composer.
Word spacing: align single word	pSingleWordAlignment:Enum	pswa	<pSingleWordAlignment:Right>
Word spacing: desired	pDesiredWordSpace:Real	pdws	<pDesiredWordSpace:1.2> Specify a value between 0 and 10 (1000%). The default value is 1.0 (100%).
Word spacing: maximum	pMaxWordSpace:Real	pmaws	<pMaxWordSpace:1.2> The value 1.0 equals 100%. The default value is 1.3 (133%). Specify a value between 0 and 10 (1000%) not less than Desired value.
Word spacing: minimum	pMinWordSpace:Real	pmiws	<pMinWordSpace:0.9> The value 1.0 equals 100%. The default value is 0.8 (80%). Specify a value between 0 and 10 (1000%) not greater than Desired value.

Table tags

For information on table and cell style definition tags, see “Start file and definition tags” on page 3.

Attribute	Tag name	Tag abbr.	Examples and notes
Table start	TableStart: <i>Real,Real, Real, Real</i>	tStart	<tStart:5,4, 1, 0> <tStart: rows, columns, header rows, footer rows>
Table end	TableEnd	tEnd	<tEnd>
Row start	RowStart	rStart	<rStart>
Row end	RowEnd	rEnd	<rEnd>
Cell start	CellStart: <i>Real,Real</i>	cStart	<cStart:1,1>
Cell end	CellEnd	cEnd	<cEnd>
Column start	ColStart	coStart	<coStart>
Start headers	tStartHeadersOn: <i>Real</i>	tshon	<tStartHeadersOn:2> Possible values are 0, 1, 2 0 = Repeat header on every text column 1 = Repeat header once per frame 2 = Repeat header once per page
Start footers	tStartFootersOn: <i>Real</i>	tsfon	<tStartFootersOn:1> Possible values are 0, 1, 2 0 = Repeat footer on every text column 1 = Repeat footer once per frame 2 = Repeat footer once per page
Skip first header	tSkipFirstHeader: <i>Boolean</i>	tsfh	<tSkipFirstHeader:1> 1=on, 0=off (default)
Skip first footer	tSkipFirstFooter: <i>Boolean</i>	tsff	<tSkipFirstFooter:1> 1=on, 0=off (default)
Cell: bottom inset	tCellAttrBottomInset: <i>Real</i>	tcabi	<tCellAttrBottomInset:9>
Cell: bottom stroke color	tCellBottomStrokeColor: <i>Definition</i>	tcbsc	<tCellBottomStrokeColor:Blue>
Cell: bottom stroke tint	tCellAttrBottomStrokeTint: <i>Real</i>	tcabst	<tCellAttrBottomStrokeTint:70>
Cell: bottom stroke gap tint	tCellBottomStrokeGapTint: <i>Real</i>	tcbsgt	<tCellBottomStrokeGapTint:95>
Cell: bottom stroke type	tcBottomStrokeType: <i>Enum</i>	tcbst	<tcBottomStrokeType:ThinThick>
Cell: bottom stroke gap color	tCellbottomStrokeGapColor: <i>Real</i>	tcbsgc	<tCellBottomStrokeGapColor:C\=100 M\=0 Y\=0 K\=0>
Cell: bottom stroke gap overprint	tCellBottomStrokeGapOverprint: <i>Boolean</i>	tcbsgo	<tCellBottomStrokeGapOverprint:0> 1=on, 0=off (default)
Cell: default cell type	tCellDefaultCellType: <i>Enum</i>	tcdct	<tCellDefaultCellType:1>
Cell: fill color	tCellFillColor: <i>Definition</i>	tcfc	<tCellFillColor:Blue>
Cell: fill tint	tCellAttrFillTint: <i>Real</i>	tcaft	<tCellAttrFillTint:20>

Attribute	Tag name	Tag abbr.	Examples and notes
Cell: first line offset	tTextCellFirstLine-Offset: <i>Enum</i>	tcflo	<tTextCellFirstLineOffset:2> Valid values include 1 (Ascent), 2 (Cap Height), 3 (Leading), 4 (x Height), and 5 (Fixed). 1 is the default.
Cell: left inset	tCellAttrLeftInset: <i>Real</i>	tcali	<tCellAttrLeftInset:9>
Cell: left stroke color	tCellLeftStrokeColor: <i>Definition</i>	tcpsc	<tCellLeftStrokeColor:Blue>
Cell: left stroke tint	tCellAttrLeftStrokeTint: <i>Real</i>	tcalst	<tCellAttrLeftStrokeTint:70>
Cell: left stroke type	tCellLeftStrokeType: <i>Enum</i>	tcclst	<tCellLeftStrokeType:ThinThick>
Cell: left stroke gap tint	tCellLeftStrokeGapTint: <i>Real</i>	tcclsgt	<tCellLeftStrokeGapTint:95>
Cell: left stroke gap color	tCellLeftStrokeGapColor: <i>Real</i>	tcclsgc	<tCellLeftStrokeGapColor:C\=100 M\=0 Y\=0 K\=0>
Cell: left stroke gap overprint	tCellLeftStrokeGap Overprint: <i>Boolean</i>	tcclsgo	<tCellLeftStrokeGapOverprint:0> 1=on, 0=off (default)
Cell: outer bottom stroke color	tCellOuterBottom StrokeColor: <i>Definition</i>	tcobsc	<tCellOuterBottomStrokeColor:Blue>
Cell: outer bottom stroke type	tCellOuterBottom StrokeType: <i>Enum</i>	tcobst	<tCellOuterBottomStrokeType:ThinThick>
Cell: outer left stroke color	tCellOuterLeft StrokeColor: <i>Definition</i>	tcosc	<tCellOuterLeftStrokeColor:Blue>
Cell: outer left stroke type	tCellOuterLeftStrokeType: <i>Enum</i>	tclost	<tCellOuterLeftStrokeType:ThinThick>
Cell: outer right stroke color	tCellOuterRight StrokeColor: <i>Definition</i>	tcorsc	<tCellOuterRightStrokeColor:Blue>
Cell: outer right stroke type	tCellOuterRightStrokeType: <i>Enum</i>	tcorst	<tCellOuterRightStrokeType:ThinThick>
Cell: outer top stroke color	tCellOuterTop StrokeColor: <i>Definition</i>	tcotsc	<tCellOuterTopStrokeColor:Blue>
Cell: outer top stroke type	tCellOuterTopStrokeType: <i>Enum</i>	tcotst	<tCellOuterTopStrokeType:ThinThick>
Cell: right inset	tCellAttrRightInset: <i>Real</i>	tcari	<tCellAttrRightInset:9>
Cell: right stroke color	tCellRightStrokeColor: <i>Definition</i>	tcpsc	<tCellRightStrokeColor:Blue>
Cell: right stroke tint	tCellAttrRightStrokeTint: <i>Real</i>	tcarst	<tCellAttrRightStrokeTint:70>
Cell: right stroke type	tCellRightStrokeType: <i>Enum</i>	tcrcst	<tCellRightStrokeType:ThinThick>
Cell: right stroke gap tint	tCellRightStroke GapTint: <i>Real</i>	tcrcsgt	<tCellRightStrokeGapTint:95>
Cell: right stroke gap color	tCellRightStroke GapColor: <i>Real</i>	tcrcsgc	<tCellRightStrokeGapColor:C\=100 M\=0 Y\=0 K\=0>
Cell: right stroke gap overprint	tCellRightStrokeGap Overprint: <i>Boolean</i>	tcrcsgo	<tCellRightStrokeGapOverprint:0> 1=on, 0=off (default)

Attribute	Tag name	Tag abbr.	Examples and notes
Cell: rotation	tCellAttrRotation: <i>Enum</i>	tcar	<tCellAttrRotation:180> Valid values include 0 (default), 90, 180, and 270.
Cell: stroke weight bottom	tCellAttrBottom Stroke-Weight: <i>Real</i>	tcabsw	<tCellAttrBottomStrokeWeight:3>
Cell: stroke weight left	tCellAttrLeft Stroke-Weight: <i>Real</i>	tcalsw	<tCellAttrLeftStrokeWeight:3>
Cell: stroke weight right	tCellAttrRight Stroke-Weight: <i>Real</i>	tcarsw	<tCellAttrRightStrokeWeight:3>
Cell: stroke weight top	tCellAttrTop Stroke-Weight: <i>Real</i>	tcatsw	<tCellAttrTopStrokeWeight:3>
Cell: top inset	tCellAttrTopInset: <i>Real</i>	tcati	<tCellAttrTopInset:9>
Cell: top stroke color	tCellTopStrokeColor: <i>Definition</i>	tctsc	<tCellTopStrokeColor:Blue>
Cell: top stroke tint	tCellAttrTopStrokeTint: <i>Real</i>	tcatst	<tCellAttrTopStrokeTint:70>
Cell: top stroke type	tTopStrokeType: <i>Enum</i>	tctst	<tTopStrokeType:ThinThick>
Cell: top stroke gap tint	tCellTopStrokeGapTint: <i>Real</i>	tctsgt	<tCellTopStrokeGapTint:95>
Cell: top stroke gap color	tCellTopStrokeGap-Color: <i>Real</i>	tctsgc	<tCellTopStrokeGapColor:C\=100 M\=0 Y\=0 K\=0>
Cell: top stroke gap overprint	tCellTopStrokeGap Overprint: <i>Boolean</i>	tctsgo	<tCellTopStrokeGapOverprint:0> 1=on, 0=off (default)
Cell: type	tCellType: <i>Enum</i>	tct	<tCellType:1>
Cell: vertical composition	tTextCellVerticalComposition: <i>Enum</i>	tcvc	<tTextCellVerticalComposition:1>
Cell: vertical justification	tTextCellVertical Justification: <i>Enum</i>	tcvj	<tTextCellVerticalJustification:2> Valid values include 0 (Top), 1 (Bottom), 2 (Center), and 3 (Justify)
Cell: vertical justification paragraph spacing limit	tTextCellAttrMaxVJ InterParaSpace: <i>Real</i>	ttcamvjips	<tTextCellAttrMaxVJInterParaSpace:40>
Column width	tColAttrWidth: <i>Real</i>	tcaw	<tColAttrWidth:120>
Column: fill pattern (first color)	tColFillPatFirstColor: <i>Enum</i>	tcfpcl	<tColFillPatFirstColor:ThinThick>
Column: fill pattern (second color)	tColFillPatSecond-Color: <i>Enum</i>	tcfpscl	<tColFillPatSecondColor:ThinThick>
Column: stroke pattern (first color)	tColStrokePatFirst-Color: <i>Enum</i>	tcspfl	<tColStrokePatFirstColor:ThinThick>
Column: stroke pattern (first type)	tColStrokePattern First-Type: <i>Enum</i>	tcspft	<tColStrokePatternFirstType:ThinThick>
Column: stroke pattern (second color)	tColStrokePat Second-Color: <i>Enum</i>	tcrspcl	<tColStrokePatSecondColor:ThinThick>
Column: stroke pattern (second type)	tColStrokePattern Second-Type: <i>Enum</i>	tcspst	<tColStrokePatternSecondType:ThinThick>

Attribute	Tag name	Tag abbr.	Examples and notes
Column: stroke pattern first weight	tColStrokePattern First-Weight: <i>Real</i>	tcspfw	<tColStrokePatternFirstWeight:9>
Column: stroke pattern second weight	tColStrokePattern Second-Weight: <i>Real</i>	tcspsw	<tColStrokePatternSecondWeight:9>
Column: stroke type	tColStrokeType: <i>Enum</i>	tcst	<tColStrokeType:ThickThin>
Row height	tRowAttrHeight: <i>Real</i>	trah	<tRowAttrHeight:20>
Row: AutoGrow	tRowAutoGrow: <i>Enum</i>	trag	<tRowAutoGrow:1>
Row: fill pattern (first color)	tRowFillPatFirstColor: <i>Enum</i>	trfpfl	<tRowFillPatFirstColor:ThinThick>
Row: fill pattern (second color)	tRowFillPat Second-Color: <i>Enum</i>	trfpscl	<tRowFillPatSecondColor:ThinThick>
Row: row size maximum	tRowAttrMaxRowSize: <i>Real</i>	tramars	<tRowAttrMaxRowSize:40>
Row: row size minimum	tRowAttrMinRowSize: <i>Real</i>	tramirs	<tRowAttrMinRowSize:9>
Row: stroke pattern (first color)	tRowStrokePat First-Color: <i>Enum</i>	trspfl	<tRowStrokePatFirstColor:ThinThick>
Row: stroke pattern (first type)	tRowStrokePattern First-Type: <i>Enum</i>	trspft	<tRowStrokePatternFirstType:ThinThick>
Row: stroke pattern (second color)	tRowStrokePat Second-Color: <i>Enum</i>	trspsc	<tRowStrokePatSecondColor:ThinThick>
Row: stroke pattern (second type)	tRowStrokePattern Second-Type: <i>Enum</i>	trspst	<tRowStrokePatternSecondType:ThinThick>
Row: stroke pattern first weight	tRowStrokePattern First-Weight: <i>Real</i>	trspfw	<tRowStrokePatternFirstWeight:9>
Row: stroke pattern second weight	tRowStrokePattern Second-Weight: <i>Real</i>	trspsw	<tRowStrokePatternSecondWeight:9>
Row: stroke type	tRowStrokeType: <i>Enum</i>	trst	<tRowStrokeType:ThickThin>
Table: column end pattern (start value)	tTableColFillPattern EndValue: <i>Real</i>	trcfpev	<tTableColFillPatternEndValue:1>
Table: column fill pattern (first count)	tTableColFillPattern First-Count: <i>Real</i>	trcfpc	<tTableColFillPatternFirstCount:2>
Table: column fill pattern (second count)	tTableColFillPattern Second-Count: <i>Real</i>	trcfpsc	<tTableColFillPatternSecondCount:2>
Table: column fill pattern (start value)	tTableColFill Pattern-StartValue: <i>Real</i>	trcfpsv	<tTableColFillPatternStartValue:1>
Table: column stroke color	tColStrokeColor: <i>Definition</i>	tcsc	<tColStrokeColor:Blue>
Table: column stroke pattern (first count)	tTableColStrokePattern First-Count: <i>Real</i>	tcspfc	<tTableColStrokePatternFirstCount:2>
Table: column stroke pattern (second count)	tTableColStrokePattern SecondCount: <i>Real</i>	tcspsc	<tTableColStrokePatternSecondCount:2>
Table: column stroke weight	tColStrokeWeight: <i>Real</i>	tcsw	<tColStrokeWeight:3>
Table: fill pattern priority	tTableFillPatternPriority: <i>Real</i>	tfpp	<tTableFillPatternPriority:1>

Attribute	Tag name	Tag abbr.	Examples and notes
Table: outer bottom stroke tint	tOuterBottom-StrokeTint: <i>Real</i>	tobst	<tOuterBottomStrokeTint:70>
Table: outer bottom stroke weight	tOuterBottom Stroke-Weight: <i>Real</i>	tobsw	<tOuterBottomStrokeWeight:3>
Table: outer left stroke tint	tOuterLeftStrokeTint: <i>Real</i>	tolst	<tOuterLeftStrokeTint:70>
Table: outer left stroke weight	tOuterLeftStroke-Weight: <i>Real</i>	tolsw	<tOuterLeftStrokeWeight:3>
Table: outer right stroke tint	tOuterRightStrokeTint: <i>Real</i>	torst	<tOuterRightStrokeTint:70>
Table: outer right stroke weight	tOuterRight Stroke-Weight: <i>Real</i>	torsw	<tOuterRightStrokeWeight:3>
Table: outer top stroke tint	tOuterTopStrokeTint: <i>Real</i>	totst	<tOuterTopStrokeTint:70>
Table: outer top stroke weight	tOuterTopStrokeWeight: <i>Real</i>	totsw	<tOuterTopStrokeWeight:3>
Table: row end pattern (start value)	tTableRowFillPattern EndValue: <i>Real</i>	trfpev	<tTableRowFillPatternEndValue:1>
Table: row fill pattern (first count)	tTableRowFillPattern First-Count: <i>Real</i>	trfpfc	<tTableRowFillPatternFirstCount:2>
Table: row fill pattern (second count)	tTableRowFillPattern SecondCount: <i>Real</i>	trfpfc	<tTableRowFillPatternSecondCount:2>
Table: row fill pattern (start value)	tTableRowFill Pattern-StartValue: <i>Real</i>	trfpsv	<tTableRowFillPatternStartValue:1>
Table: row keeps	tRowKeeps: <i>Real</i>	trk	<tRowKeeps:3>
Table: row stroke color	tRowStrokeColor: <i>Definition</i>	trsc	<tRowStrokeColor:Blue>
Table: row stroke pattern (first count)	tTableRowStrokePattern FirstCount: <i>Real</i>	trspfc	<tTableRowStrokePatternFirstCount:2>
Table: row stroke pattern (first count)	tTableRowStrokePattern SecondCount: <i>Real</i>	trspsc	<tTableRowStrokePatternSecondCount:2>
Table: row stroke weight	tRowStrokeWeight: <i>Real</i>	trsw	<tRowStrokeWeight:3>
Table: stroke drawing order	tStrokeOrder: <i>Real</i>	tso	<tStrokeOrder:3> Possible values are 0-3: 0 - Best Join 1 - Row Strokes in Front 2 - Column Strokes in Front 3 - InDesign 2.0 Compatibility
Table: spacing after	tAfterSpace: <i>Real</i>	tas	<tAfterSpace:9>
Table: spacing before	tBeforeSpace: <i>Real</i>	tbs	<tBeforeSpace:9>

Hyperlink and index tags

Attribute	Tag name	Tag abbr.	Examples and notes
Hyperlink	Hyperlink: <i>Definition</i>	hpl	<Hyperlink>=<HyperlinkName:Page 3>>
Hyperlink destination definition	HyperlinkDestDefn: <i>Definition</i>	hpldestdfn	<HyperlinkDestDefn:=<HyperlinkName:Page 3>>
Hyperlink name	HyperlinkName: <i>Real</i>	hplname	<HyperlinkName:Page 3>
Hyperlink destination	HyperlinkDest: <i>Real</i>	hpldest	<HyperlinkDest:Chapter 1>
Hyperlink length	HyperlinkLength: <i>Real</i>	hpllen	<HyperlinkLength:6> Specify the number of characters in the hyperlink.
Hyperlink destination name	HyperlinkDestName: <i>Real</i>	hpldestname	<HyperlinkDestName:Page 3>
Hyperlink destination URL	HyperlinkDestUrl: <i>Real</i>	hpldesturl	<HyperlinkDestUrl:http://www.adobe.com>
Hyperlink destination index	HyperlinkDestIndex: <i>Real</i>	hpldestidx	<HyperlinkDestIndex:1>
Hyperlink destination page	HyperlinkDestPage: <i>Real</i>	hpldestpage	<HyperlinkDestPage:3>
Hyperlink destination page zoom type	HyperlinkDestPageZoomType: <i>Real</i>	hpldestpage-zoomtype	<HyperlinkDestPageZoomType:Fixed> Valid values include Fixed, Fit View, Fit in Window, Fit Width, Fit Height, Fit Visible, and Inherit Zoom.
Hyperlink destination page zoom factor	HyperlinkDestPageZoomFactor: <i>Real</i>	hpldestpage-zoomfactor	<HyperlinkDestPageZoomFactor:1.7> 1=100% magnification
Hyperlink hidden	Hidden: <i>Boolean</i>	hid	<Hidden:0>
Hyperlink border width	BrdrWidth: <i>Real</i>	brdrw	<BrdrWidth:2>
Hyperlink border visible	BrdrVisible: <i>Boolean</i>	brdrv	<BrdrVisible:1>
Hyperlink border highlight	BrdrHilight: <i>Boolean</i>	brdrh	<BrdrHilight:1>
Hyperlink border style	BrdrStyle: <i>Enum</i>	brdrs	<BrdrStyle:1>
Hyperlink border color	BrdrColor: <i>Real</i>	brdrc	<BrdrColor:Blue>
Index entry	IndexEntry	idx	<IndexEntryType:IndexPageEntry> <IndexEntryStyleUid:0><IndexEntryRangeType:kCurrentPage><IndexEntryDisplayString:simple page index>>
Index entry type	IndexEntryType	IdxEnType	<IndexEntryType:IndexPageEntry>
Index entry range type	IndexEntryRangeType	IdxEnRng-Type	<IndexEntryRangeType:kForNextNParagraphs>
Index entry style	IndexEntryStyle	IdxEnStyle	<IndexEntryStyle:MyStyle>
Index entry next style	IndexEntryNextStyle	IdxEnNxt-Style	<IndexEntryNextStyle:MyStyle>
Index entry number of paragraph or page	IndexEntryNumParOrPage	IdxEn-NumPgOrPar	<IndexEntryNumParOrPage:30>
Index entry display string	IndexEntryDisplayString	IdxEnDispStr	<IndexEntryDisplayString:simple page index>

Attribute	Tag name	Tag abbr.	Examples and notes
Index entry sorting string	IndexEntrySortString	IdxEnSortStr	<IndexEntrySortString:An index>
Index cross-reference entry type	IndexXRefEntryType	IdxXrEnType	<IndexXRefEntryType:kSeeHerein>
Index cross-reference entry custom string	IndexXRefEntryCustomString	IdxXrEnCusStr	<IndexXRefEntryCustomString:abc>

Footnote tags

Attribute	Tag name	Tag abbr.	Examples and notes
Footnote start	FootnoteStart	fnStart	<FootnoteStart:>
Footnote end	FootnoteEnd	fnEnd	<FootnoteEnd:>

Bullets and numbering tags

The following InDesign CS2 tags are no longer available in InDesign CS3: bnSize (bnsz), bnColor (bnc), bnSeparator (bnsep), numFont (nmf), and numTypeFace (nmtf). These tags are imported in InDesign CS3 as text.

Attribute	Tag name	Tag abbr.	Examples and notes
List type	bnListType: <i>Enum</i>	bnlt	<bnListType:Bullet> Valid values include Bullet and Numbered.
Numbering style for bullets and numbering	bnNumberingStyle: <i>Enum</i>	bnns	<bnNumberingStyle:01\,02\,03\,04...> Valid values include the items that can be selected from the Format menu, including 1\, 2\, 3\, 4... and a\, b\, c\, d...
Number start at	bnNumberStartAt: <i>Integer</i>	bnnsa	<bnNumberStartAt:7>
Bullet character	bnBulletCharacter: <i>Unicode setting,String</i>	bnbc	<bnBulletCharacter:UnicodeOnly\,9674> Valid values can be UnicodeOnly or UnicodeWithFont followed by the unicode value.
Number expression	numNumber: <i>String</i>	nmnum	<numNumber:^H.^#> Valid strings include the characters and number placeholders inserted in the Number field.
List level	numListLevel: <i>Enum</i>	nmll	<numListLevel:2> Valid integers range from 1 to 9.
Bullet alignment	bulAlignment: <i>Enum</i>	bla	<bulAlignment:Center> Valid values include Left, Right, and Center.
Number alignment	numAlignment: <i>Enum</i>	nma	<numAlignment:Center> Valid values include Left, Right, and Center.
Bullet character style used	bulCharStyle: <i>Definition</i>	blcs	<bulCharStyle:Emphasis> Valid values include character style names in the current document.

Attribute	Tag name	Tag abbr.	Examples and notes
Number character style used	<i>numCharStyle:Definition</i>	nmcs	<bulCharStyle:Emphasis> Valid values include character style names in the current document.
Restart numbering	<i>numShouldRestart:Boolean</i>	nmsr	<numShouldRestart:1> 1=restart numbering; 0=don't restart
Continue numbering from previous	<i>numCFPrevious:Boolean</i>	nmcfp	<numCFPrevious:1> 1=continues numbering from previous; 0=don't continue numbering
List name	<i>numListName:Definition</i>	nmln	<numListName:Level 1> Valid values include defined list names in the current document.
Restart policy	<i>numRestartPolicy:Enum</i>	nmrp	<numRestartPolicy:LevelRange\,2\,4> Valid values include LevelRange (“\,2\,4” restarts levels 2 through 4) and Specific Level (“\,3\,3” restarts numbers after level 3).
Text after bullet	<i>bulTextAfter:String</i>	blta	<bulTextAfter:\^t>

Variable tags

For information on the variable definition tag, see “Start file and definition tags” on page 3.

Attribute	Tag name	Tag abbr.	Examples and notes
Text Before	<i>tvTextBefore:String</i>	tvtb	<tvTextBefore:Chapter >
Text After	<i>tvTextAfter:String</i>	tvta	<tvTextAfter: out of>
Date Format	<i>tvDateFormat:Enum</i>	tvdf	<tvDateFormat:ddMMMMyyyy> For valid formats, see the table in the text variables section of help.
Custom text string	<i>tvString:String</i>	tvsv	<tvString:Maria Sanchez>
Numbering style	<i>tvNumStyle:Enum</i>	tvnst	<tvNumStyle:SmallLetter> Valid values include SmallLetter, LargeLetter, SmallRoman, LargeRoman, and Arabic. If not specified, the current numbering style is used.
Scope	<i>tvScope:Enum</i>	tvsc	<tvScope:Document> Valid values include Document and Section.
Folder path	<i>tvIncFolderPath:Boolean</i>	tvifp	<tvFolderPath:1> (1=include path; 0=don't include path)
File extension	<i>tvFileExtn:Boolean</i>	tvfe	<tvFileExtn:1> (1=include extension; 0=don't include extension)
Delete end punctuation	<i>tvDelEndPunc:Boolean</i>	tvdep	<tvDelEndPunc:1> (1=delete end punctuation; 0=don't delete)

Attribute	Tag name	Tag abbr.	Examples and notes
Change case	tvChangeCase:Enum	tvcc	<tvChangeCase:LowerCase> Valid values include LowerCase, UpperCase, TitleCase, and SentenceCase. If not specified, case is not changed.
Style	tvStyle:Definition	tvS	<tvStyle:Head1> Valid values include paragraph and character style names in the current document.
Use first or last style on page	tvUse:Enum	tvu	<tvUse:FirstInPage> Valid values include FirstInPage and LastInPage.

InDesign tags for special characters

If you want to add special characters into a tagged text file, type the following values into the tagged text file:

Special character	Value
Paragraph return (hard return)	<0x000D>
End of line (soft return)	<0x000A>
Auto page numbering	<0xE0018>
Section marker	<0xE0019>
Bullet character	<0x2022>
Copyright symbol	<0x00A9>
Degree symbol	<0x00B0>
Ellipsis	<0x2026>
Paragraph symbol	<0x00B6>
Registered trademark symbol	<0x00AE>
Section symbol	<0x00A7>
Trademark symbol	<0x2122>
Em dash	<0x2014>
En dash	<0x2013>
Em space	<0x2003>
Ideographic space	<0x3000>
En space	<0x2002>
Flush space	<0x2001>
Hair space	<0x200A>
Sixth space	<0x2006>
Quarter space	<0x2005>
Third space	<0x2004>
Punctuation space	<0x2008>

Special character	Value
Figure space	<0x2007>
Flush space	<0x2001>
Nonbreaking space	<0x00A0>
Nonbreaking space (fixed width)	<0x202F>
Thin space	<0x2009>
Discretionary hyphen	<0x00AD>
Nonbreaking hyphen	<0x2011>
Double left quotation mark	<0x201C>
Double right quotation mark	<0x201D>
Single left quotation mark	<0x2018>
Single right quotation mark	<0x2019>
Non-joiner	<0x200C>

